



| CABLE LENGTH | CABLE P/N    | GRIPLOCK P/N      |
|--------------|--------------|-------------------|
| 24           | AG-16-44-24  | G-AG16-44-GHA-24  |
| 48           | AG-16-44-48  | G-AG16-44-GHA-48  |
| 72           | AG-16-44-72  | G-AG16-44-GHA-72  |
| 96           | AG-16-44-96  | G-AG16-44-GHA-96  |
| 120          | AG-16-44-120 | G-AG16-44-GHA-120 |
| 150          | AG-16-44-150 | G-AG16-44-GHA-150 |
| 180          | AG-16-44-180 | G-AG16-44-GHA-180 |
| 240          | AG-16-44-240 | G-AG16-44-GHA-240 |

**PROPRIETARY AND CONFIDENTIAL**  
 This drawing and these specifications are the exclusive property of GRIPLOCK SYSTEMS INC. and shall not be divulged, reproduced, copied, or used as the basis for the manufacture or sale of apparatus without the express written authorization of GRIPLOCK SYSTEMS INC.

REF: \_\_\_\_\_ DATE: 09/28/06

MATERIAL: NA

SCALE: 1:1 FILE: G-AG16-44-GHA-xxx

**GRIPLOCK SYSTEMS**  
 410 Palm Ave. Loft A18, Carpinteria, CA 93013  
 Phone (805) 566-0064 Fax (805) 566-0065

GRIPLOCK P/N: G-AG16-44-GHA-xxx

DESCRIPTION: 1/16" Galvanized Looped Cable with ZF-15-GHA

**GRIPLOCK SYSTEMS**